CCTV SOLAR POWER SUPPLY SYSTEM

CCTV Solar Power Supply System

Model CS3015 (30W15AH12.8V)

CS3015 I 30W15Ah 192Wh Solar Power System

The CS3015 30W Solar Power System is equipped with a 15Ah (192Wh) $LiFePO_4$ battery, providing reliable and stable off-grid power for small outdoor applications.

Designed with a compact structure for easy installation, it is ideal for powering CCTV cameras, 4G routers, and remote monitoring devices. Built for durability and long-term performance, the system ensures continuous and uninterrupted power supply in areas without grid access.

Perfect for residential, garden, and small-scale surveillance or monitoring applications.

Features

- Solar-Powered & Plug-and-Play – No external power required; install anywhere with stable, reliable output.
- Durable & Safe Design – Anti-microcrack, low internal loss, high safety, and low-temperature performance.
- Flexible & Easy Installation – U-shaped clamps; compatible with various poles; no drilling required.
- Remote Monitoring Support – RS485 communication for easy system management.
- Smart Energy Management – Automatically optimizes power generation and storage for maximum efficiency.
- IP65 Battery Protection – Fully weatherproof for outdoor installation.
- High-Quality Materials – Corrosion-resistant frame, stainless steel screws, and waterproof connection cables.
- Anti-Vibration Structure – Reduces impact on optical instruments and video image quality in pole/tower setups.

Specification

MAXSOL New Zealand

CS3015 (15Ah12.8V 192Wh)

Solar Panel Spec

Communication interface	RS485 (Optional)
Maximum Power	30W (1000W/㎡ standard lighting test conditions)
Open circuit voltage	22VDC
Maximum current	4.4A
Solar Panel Dimensions	530mm*350mm*25mm

Battery Spec

Solution	MPPT (input maximum power tracking algorithm), constant voltage output
Battery capacity	12.8V/15AH (192WH)
Charging indication	LED status indicator
Charging Voltage	15-18VDC
Maximum charging current	6A
Output Voltage	12±0.2VDC
Maximum output current	3A (total of 2 outputs)
Battery Pack overcharge voltage	14.6VDC
Battery Pack over-discharge voltage	10VDC
Input Interface	Photovoltaic aviation plug
Output Interface	DC5.5mm diameter standard male plug, 2 outputs in total
Power on power consumption	0.5±0.1W (normal temperature, no load when powered on)
Waterproof Level	IP65
Storage Temperature	0~45℃
Operating Temperature	Charging: -10~50℃; Discharging: -10~60℃
Battery Case Dimensions	IP65, 500mm*98mm*82mm

Battery Life

Shelf Life (Power Off State)	Up to 2 years (No output after shutdown; self-discharge rate approx. 3%–5% per month under normal conditions)
Standby Time (No Load, Powered On)	Approx. 20 days (At normal temperature conditions)
Operating Time (With Load)	Actual operating time depends on the connected load, battery capacity and operating conditions. For reference, the system runtime can be estimated by dividing the usable battery capacity (Wh) by the total load power (W), assuming no solar charging.
Recharge Time (0–100%)	Approx. 2–3 days under standard sunlight conditions (4–5 peak sun hours per day, normal temperature). Actual charging time may vary depending on sunlight intensity, system efficiency and power consumption.

All-in-One Package

Size	720*360*225MM
Weight (Include bracket and accessories)	8.05KG
Certificate	CE, MSDS, UN38.3, DGM, Sea Transportation Certificate

Dimension



Widely Used Applications

The Solar Power Supply system is widely used in various outdoor surveillance and communication applications, including:

- CCTV surveillance systems
- Solar-powered security and monitoring systems
- 4G/5G wireless routers and communication devices
- Remote and off-grid monitoring stations
- Road and traffic surveillance projects
- Construction site security systems
- Farms, plantations, and agricultural monitoring
- Industrial and perimeter security applications
- Smart city and infrastructure projects

Contact us

Maxsol New Zealand

Email

sales@maxsol-tech.com